

VESMETAL

Masche: (R) 200 x 75

aus Stahlblech (Materialdicke: 2,5 - 6,0mm / max. Tafelbreite: 2500mm)

Kurzbezeichnung Bestell-Nr.	Maschen- länge mm L	Maschen- weite mm W (±5%)	Stegbreite mm B (±5%)	Material- dicke mm A (±10%)	Streckgitter- dicke mm D	Streckgitterbreiten (max.) ± 10%		freier Quer- schnitt	Gewicht Kg/m ² ≙
						1250	2500		
200/3020	200	75	3,0	2,0	6,0	X	X	92%	1,28
200/12025	200	75	12,0	2,5		X	X	68%	6,39
200/4530	200	75	4,5	3,0	9,2	X	X	88%	2,88
200/6030	200	75	6,0	3,0	12,2	X	X	84%	3,84
200/15030	200	75	15,0	3,0		X	X	60%	9,60
200/6040	200	75	6,0	4,0	12,4	X	X	84%	5,12
200/12040	200	75	12,0	4,0		X	X	68%	10,23
200/7050	200	75	7,0	5,0	14,0	X	X	81%	7,47
200/8060	200	75	8,0	6,0	17,0	X	X	79%	10,24
200/10060	200	75	10,0	6,0		X	X	73%	12,80
200/15060	200	75	12,0	6,0		X	X	68%	15,34

aus Aluminium (Materialdicke: 2,5 - 6,0mm / max. Tafelbreite: 2500mm)

Kurzbezeichnung Bestell-Nr.	Maschen- länge mm L	Maschen- weite mm W (±5%)	Stegbreite mm B (±5%)	Material- dicke mm A (±10%)	Streckgitter- dicke mm D	Streckgitterbreiten (max.) ± 10%		freier Quer- schnitt	Gewicht Kg/m ² ≙
						1250	2500		
200/3020	200	75	3,0	2,0	6,0	X	X	92%	0,44
200/12025	200	75	12,0	2,5		X	X	68%	2,16
200/4530	200	75	4,5	3,0	9,2	X	X	88%	0,98
200/6030	200	75	6,0	3,0	12,2	X	X	84%	1,30
200/15030	200	75	15,0	3,0		X	X	60%	3,24
200/6040	200	75	6,0	4,0	12,4	X	X	84%	1,73
200/12040	200	75	12,0	4,0		X	X	68%	3,46
200/7050	200	75	7,0	5,0	14,0	X	X	81%	2,52
200/8060	200	75	8,0	6,0	17,0	X	X	79%	3,46
200/10060	200	75	10,0	6,0		X	X	73%	4,32
200/15060	200	75	12,0	6,0		X	X	68%	5,18

aus Edelstahl 1.4301 (Materialdicke: 2,5 – 4,0mm / max. Tafelbreite: 2500mm)

Kurzbezeichnung Bestell-Nr.	Maschen- länge mm L	Maschen- weite mm W (±5%)	Stegbreite mm B (±5%)	Material- dicke mm A (±10%)	Streckgitter- dicke mm D	Streckgitterbreiten (max.) ± 10%		freier Quer- schnitt	Gewicht Kg/m ² ≙
						1250	2500		
200/3020	200	75	3,0	2,0	6,0	X	X	92%	1,28
200/12025	200	75	12,0	2,5		X	X	68%	6,39
200/4530	200	75	4,5	3,0	9,2	X	X	88%	2,88
200/6030	200	75	6,0	3,0	12,2	X	X	84%	3,84
200/15030	200	75	15,0	3,0		X	X	60%	9,60
200/6040	200	75	6,0	4,0	12,4	X	X	84%	5,12
200/12040	200	75	12,0	4,0		X	X	68%	10,23

aus Kupfer (Materialdicke: 2,5 – 5,0mm / max. Tafelbreite: 2500mm)

Kurzbezeichnung Bestell-Nr.	Maschen- länge mm L	Maschen- weite mm W (±5%)	Stegbreite mm B (±5%)	Material- dicke mm A (±10%)	Streckgitter- dicke mm D	Streckgitterbreiten (max.) ± 10%		freier Quer- schnitt	Gewicht Kg/m ² ≙
						1250	2500		
200/3020	200	75	3,0	2,0	6,0	X	X	92%	1,43
200/12025	200	75	12,0	2,5		X	X	68%	7,11
200/4530	200	75	4,5	3,0	9,2	X	X	88%	3,21
200/6030	200	75	6,0	3,0	12,2	X	X	84%	4,28
200/15030	200	75	15,0	3,0		X	X	60%	10,68
200/6040	200	75	6,0	4,0	12,4	X	X	84%	5,70
200/12040	200	75	12,0	4,0		X	X	68%	11,38
200/7050	200	75	7,0	5,0	14,0	X	X	81%	8,31

Alle Angaben unter jeglichen Vorbehalt !!!