

VESMETAL

Masche: (R) 200 x 100

aus Stahlblech (Materialdicke: 2,5 - 6,0mm / max. Tafelbreite: 2500mm)

Kurzbezeichnung Bestell-Nr.	Maschen- länge mm L	Maschen- weite mm W (±5%)	Stegbreite mm B (±5%)	Material- dicke mm A (±10%)	Streckgitter- dicke mm D	Streckgitterbreiten (max.) ± 10%		freier Quer- schnitt	Gewicht Kg/m ² ≙
						1250	2500		
200/100-3030	200	100	3,0	3,0	8,0	X	X	94%	1,44
200/100-4030	200	100	4,0	3,0	8,5	X	X	92%	1,92
200/100-5040	200	100	5,0	4,0	11,0	X	X	90%	3,20
200/100-6040	200	100	6,0	4,0	11,8	X	X	88%	3,84
200/100-12040	200	100	12,0	4,0		X	X	76%	7,68
200/100-6050	200	100	6,0	5,0	11,9	X	X	88%	4,80
200/100-8050	200	100	8,0	5,0	12,8	X	X	84%	6,40
200/100-7060	200	100	7,0	6,0	13,5	X	X	86%	6,72
200/100-9060	200	100	9,0	6,0	17,0	X	X	82%	8,64
200/100-10060	200	100	10,0	6,0	19,5	X	X	80%	9,60
200/100-15060	200	100	15,0	6,0		X	X	70%	14,38

aus Aluminium (Materialdicke: 2,5 - 6,0mm / max. Tafelbreite: 2500mm)

Kurzbezeichnung Bestell-Nr.	Maschen- länge mm L	Maschen- weite mm W (±5%)	Stegbreite mm B (±5%)	Material- dicke mm A (±10%)	Streckgitter- dicke mm D	Streckgitterbreiten (max.) ± 10%		freier Quer- schnitt	Gewicht Kg/m ² ≙
						1250	2500		
200/100-3030	200	100	3,0	3,0	8,0	X	X	94%	0,49
200/100-4030	200	100	4,0	3,0	8,5	X	X	92%	0,65
200/100-5040	200	100	5,0	4,0	11,0	X	X	90%	1,08
200/100-6040	200	100	6,0	4,0	11,8	X	X	88%	1,30
200/100-12040	200	100	12,0	4,0		X	X	76%	2,59
200/100-6050	200	100	6,0	5,0	11,9	X	X	88%	1,62
200/100-8050	200	100	8,0	5,0	12,8	X	X	84%	2,16
200/100-7060	200	100	7,0	6,0	13,5	X	X	86%	2,27
200/100-9060	200	100	9,0	6,0	17,0	X	X	82%	2,92
200/100-10060	200	100	10,0	6,0	19,5	X	X	80%	3,24
200/100-15060	200	100	15,0	6,0		X	X	70%	4,86

aus Edelstahl 1.4301 (Materialdicke: 2,5 – 4,0mm / max. Tafelbreite: 2500mm)

Kurzbezeichnung Bestell-Nr.	Maschen- länge mm L	Maschen- weite mm W (±5%)	Stegbreite mm B (±5%)	Material- dicke mm A (±10%)	Streckgitter- dicke mm D	Streckgitterbreiten (max.) ± 10%		freier Quer- schnitt	Gewicht Kg/m ² ≙
						1250	2500		
200/100-3030	200	100	3,0	3,0	8,0	X	X	94%	1,44
200/100-4030	200	100	4,0	3,0	8,5	X	X	92%	1,92
200/100-10030	200	100	10,0	3,0		X	X	80%	4,80
200/100-5040	200	100	5,0	4,0	11,0	X	X	90%	3,20
200/100-6040	200	100	6,0	4,0	11,8	X	X	88%	3,84
200/100-12040	200	100	12,0	4,0		X	X	76%	7,68
200/100-15040	200	100	15,0	4,0		X	X	70%	9,59

aus Kupfer (Materialdicke: 2,5 – 5,0mm / max. Tafelbreite: 2500mm)

Kurzbezeichnung Bestell-Nr.	Maschen- länge mm L	Maschen- weite mm W (±5%)	Stegbreite mm B (±5%)	Material- dicke mm A (±10%)	Streckgitter- dicke mm D	Streckgitterbreiten (max.) ± 10%		freier Quer- schnitt	Gewicht Kg/m ² ≙
						1250	2500		
200/100-3030	200	100	3,0	3,0	8,0	X	X	94%	1,61
200/100-4030	200	100	4,0	3,0	8,5	X	X	92%	2,14
200/100-5040	200	100	5,0	4,0	11,0	X	X	90%	3,56
200/100-6040	200	100	6,0	4,0	11,8	X	X	88%	4,27
200/100-12040	200	100	12,0	4,0		X	X	76%	8,54
200/100-6050	200	100	6,0	5,0	11,9	X	X	88%	5,34
200/100-8050	200	100	8,0	5,0	12,8	X	X	84%	7,12
200/100-15050	200	100	15,0	5,0		X	X	70%	13,33

Alle Angaben unter jeglichen Vorbehalt !!!